



STR

Standard Ring

Kroužková mechanika délka-počet kroužků- průměr kroužku (šířka základny)	ABC**									kg /1000	m ³ /karton
80											
STR 123-2-13(17)	B	80	8,5	17	16	114	2,6x1,6	500	30.000	19,0	0,0220
STR 112-2-16(15)	C	80	11	20	19	105		1200		14,5	
STR 123-2-16(17)	B	80	11	20	21	114	2,9x1,8	500	27.000	20,0	0,0220
STR 123-2-20(21)	A	80	14	24	23	115	3,4x2,2	670	20.100	22,0	0,0415
STR 123-2-25(21)	A	80	19	31	30	115	3,4x2,2	600	18.000	22,4	0,0415
STR 123-2-30(21)	A	80	24	34	34	115	3,4x2,2	400	16.000	29,0	0,0415
STR 132-2-35(27)	C	80	30	40	42	123	4,0x2,5	320	9.600	51,0	0,0450
STR 132-2-38(27)	B	80	33	45	46	123	4,5x3,2	320	9.600	59,0	0,0360
STR 132-2-45(27)	C	80	40	51	53	123	4,5x3,2	320	8.000	68,0	0,0510
STR 132-2-50(27)	C	80	45	56	57	123	4,5x3,2	250	7.500	71,0	0,0428
STR 132-2-55(38)	D	80	46	63	61	123	5,5x3,8	140	4.200	111,0	0,0428
STR 132-2-65(38)	D	80	55	73	71	123	5,5x3,8	140	4.200	124,0	0,0450
21-70-21											
STR 142-4-13(15)	D	21-70-21	9	17	15	134	2,8x1,8	700	33.600	20,5	0,0229
STR 142-4-16(15)	D	21-70-21	12	20	19	134	2,8x1,8	640	30.720	21,5	0,0229
STR 152-4-20(21)	D	21-70-21	14	24	23	144	3,4x2,2	350	16.800	40,0	0,0229
STR 152-4-23(21)	D	21-70-21	16	28	28	144	3,4x2,2	300	14.400	42,0	0,0229
STR 152-4-30(21)	D	21-70-21	24	34	34	144	3,4x2,2	250	12.000	47,0	0,0229
STR 152-4-29(27)	D	21-70-21	24	34	34	144	4,0x2,5	175	8.400	63,0	0,0229
STR 152-4-35(27)	D	21-70-21	30	40	41	144	4,0x2,5	150	7.200	70,0	0,0229
STR 152-4-38(27)	D	21-70-21	33	45	45	144	4,5x3,2	125	6.000	74,0	0,0229
STR 152-4-45(27)	D	21-70-21	40	51	53	144	4,5x3,2	125	6.000	102,0	0,0229
STR 152-4-50(27)	D	21-70-21	45	56	57	144	4,5x3,2	100	4.500	107,0	0,0229
20-80-20											
STR 158-4-20(21)	D	20-80-20	14	24	23	147	3,4x2,2	350	16.800	42,0	0,0229
STR 158-4-25(21)	D	20-80-20	19	31	30	147	3,4x2,2	250	12.000	47,0	0,0229
STR 160-4-29(27)	D	20-80-20	24	34	34	152	4,0x2,5	175	8.400	64,0	0,0229
45-65-45											
STR 212-4-13(15)	D	45-65-45	9	17	15	204	2,8x1,8	750	27.000	27,0	0,0360
STR 212-4-16(15)	C	45-65-45	12	20	19	204	2,8x1,8	700	25.200	28,0	0,0360
STR 210-4-20(21)	B	45-65-45	14	24	23	199	3,4x2,2	400	12.000	52,0	0,0405
STR 210-4-25(21)	B	45-65-45	19	31	30	199	3,4x2,2	330	9.900	55,0	0,0388
STR 210-4-30(21)	C	45-65-45	24	34	34	199	3,4x2,2	290	8.700	60,0	0,0388
STR 210-4-35(27)	C	45-65-45	30	40	41	199	4,0x2,5	160	5.760	84,0	0,0388
STR 210-4-38(27)	C	45-65-45	33	45	45	199	4,5x3,2	160	5.760	105,0	0,0360
STR 210-4-50(27)	D	45-65-45	45	56	57	199	4,5x3,2	125	4.500	125,0	0,0360

80-80-80											
STR 272-4-13(15)	B	80-80-80	9	17	15	265,5	2,8x1,8	500	20.000	38,0	0,0326
STR 272-4-16(15)	B	80-80-80	12	20	19	265,5	2,8x1,8	500	20.000	39,0	0,0326
SXR 272-4-16(15)*	A	80-80-80	11	20	19	265,5	2,8x1,8	600	18.000	39,0	0,0415
STR 290-4-20(21)	A	80-80-80	14	24	23	281,5	3,4x2,2	250	10.000	64,0	0,0326
STR 290-4-25(21)	A	80-80-80	19	31	30	281,5	3,4x2,2	250	8.750	70,0	0,0383
STR 290-4-30(21)	A	80-80-80	24	34	34	281,5	3,4x2,2	210	7.350	73,0	0,0370
STR 290-4-35(27)	B	80-80-80	30	40	41	281,5	4,0x2,5	160	4.800	112,0	0,0432
STR 290-4-38(27)	B	80-80-80	33	45	45	281,5	4,5x3,2	125	4.375	121,0	0,0383
STR 290-4-50(27)*	B	80-80-80	45	56	57	2x140,8	4,5x3,2	110	3.300	156,0	0,0432

* Připevnění i 3. nýtem uprostřed

** A - mechanika dostupná obvykle do 14 dnů

** B - mechanika dostupná obvykle do 30 dnů

** C - dodací termín do 60 dnů, objednáací minimum na dotaz

** D - dodací termín i objednáací minimum na dotaz